

JUNG PUMPEN®

U3KS

GENERAL PURPOSE SUBMERSIBLE DRAINAGE PUMP 10mm FREE PASSAGE



YEARS WARRANTY

FEATURES

Safe to run dry.

Continuous operation.

Low level pumping.

Flushing device.

Moisture sealed cable inlet.

Built in level control.

Max. head - 7m.

Max. flow - 105lpm.

APPLICATIONS

- Domestic waste water (without faecal matter).
- Rainwater.
- Drainage.
- Lightly polluted water.

PUMP CONSTRUCTION MATERIALS

Vertical, single-stage, submersible, foot strainer with 10mm free passage – detachable for activating low level pumping. Spiral casing with 11/4" BSP (male) radial pressure branch and integrated swing-type check valve, spiral casing with flushing device for drain cleaning, EIP technology hydraulics with open 5-blade impeller.

Pump casing: Glass reinforced plastic. Impeller: Glass reinforced plastic. Wear plate: Glass reinforced plastic.

Motor shaft: 304SS.

Mechanical seal: Three-fold radial shaft seal ring incorporating an intermediate oil

chamber.

OPERATING CONDITIONS

Drainage pump for the disposal of faecal free waste water, including rainwater and lightly polluted water containing particles up to 10mm. Install pump vertically (hose connection possible).

pH range: >4,5 - <12.

ELECTRICAL DATA

T	уре			Frequency Hz				Current		Insulation	IP Rating	
					P1	P2	min	ampere	protection	class		
U	3KS	1-phase	230	50	0.32	0.20	2720	1.4 A	Auto	В	68	

DIMENSIONS

2.1	Maximum Height x Width x Depth	Discharge branch	Free passage	Cable quality		approx.	operating	Intermittent temperature maximum
U3KS	255 x 220 x 280 mm	1¼" BSP (male)	10 mm	H07RN-F	10 m	4.3 kg	0° - 35°	60°

PERFORMANCE

Туре	P/No	Delivery head [m]	1	2	3	4	5	6
U3KS	JP09484	Flow rate Q [lpm]	105	98	85	70	50	29

PERFORMANCE CURVE





