

MINIBLAZE SINGLE IMPELLER PETROL PUMP

Horizontal, single-stage, surface mounted centrifugal pump with closed impeller for pumping debris-free water coupled to a reliable 2.5HP (152F) engine.

KEY FEATURES

- Lightweight high grade corrosion resistant materials
- Reliable 2.5HP engine
- Strong and durable construction
- Max. head 21m
- Max. flow 2151pm

ONGA.COM.AU

ENGINE DATA

Туре	Engine Model	Nominal kW @ 3600 RPM	Displacement CC	Fuel tank capacity	Fuel	Fuel consumption	Recommended oil type	Oil capacity
MB25L	148F-2F	1.7	79.77	1.6 litres	Unleaded	395 g/kW-h	SAE 10W-30	0.35 litres

DIMENSIONS

Туре		Pump L x W x H			Outlets	Packed L x W x H	Packed weight
	MB25L	427 x 332 x 363 mm	13.5kg	1" BSP (male)	1" BSP (male)	445 x 340 x 365 mm	15kg

PERFORMANCE



CONSTRUCTION MATERIALS

Component	Material	
Pump casing	Powder coated Aluminium	
Impeller/s	30% Glass Filled Nylon	
Diffuser	Aluminium	
Priming/discharge caps	Polypropylene	
Seal flexible bellows	Nitrile	
Seal stationary face	Ceramic	
Seal rotating face	Carbon	
Seal spring	Stainless Steel	
Motor shaft	Mild Steel	
O'Rings	Nitrile	

OPERATING CONDITIONS

Fluid:	Water
Max. Water temperature:	40°C
Min. Water temperature:	1°C
Max. Ambient temperature:	40°C*

*Engine performance greatly reduced w/ increased ambient temperature and/or altitude.

Suitable for pumping clean non-aggressive liquids without solids or fibres in suspension.



APPLICATIONS

	Fire fighting.	
≈ ∢ 91 1 −	Water transfer.	
Ľ.	Ute packs and spray units.	
3	Water evacuation.	

PENTAIR

1-21 Monash Drive | Dandenong South, VIC 3175 | Australia | 1300 137 344 | pentair.com.au

Information contained here-in remains the property of Pentair Australia Holdings Pty Ltd under Australian copyright law. Content may not be reproduced or transmitted without our prior written permission.

Disclaimer: Pentair reserves the right to change product specifications and products details. Product images are for reference purposes only and my not represent the actual/current product.